TDS

ACRYLIC VARNISH



DESCRIPTION

Transparent acrylic varnish for the care of coated and uncoated surfaces such as wood, metal, aluminum, and stone. This clear lacquer has excellent adhesion, long-lasting gloss, and good weather resistance.

PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm³/20°C, ASTM D – 1475)
- VOC content: 600 g/L
- Flash Point: -104°C (based on propellant)
- Drying time
  - Touch (20°C, Humidity<65%): 5-10min
  - Through dry (20°C, Humidity <65%): 1h
  - Maximum hardness: 24h
- Coverage: 5m²/L
- Gloss: 80-90 GLOSS UNIT/GLOSS (N376)
  0-4 GLOSS UNIT/MATTE (N377)
  20-50 GLOSS UNIT/SATINE (N378)
  (GLOSS METER 60°ASTM D – 1471)
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 400ml

INSTRUCTIONS FOR USE

APPLICATION
Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. Apply the primer in several thin layers. For better results apply 2-3 thin coats, 3-5 min apart. **Best application temperature: 10-25°C.**

AFTER USE
Spray holding the can inverted for 3''. Clean the caps with solvent.

STORAGE
5°C-35°C. Never leave the product inside a vehicle.

CAP SYSTEM

FINE CAP WHITE/BEIGE
- Less overspray
- Smooth finish
- Even coating
- Fast drying

SAFETY

Request SDS

ISSUED DATE: 22/10/2026 **VERSION:** 03

COSMOS LAC S.A.
PAINT INDUSTRY
©2026
PLITHONOS GEMISTOU 1, KALLITHEA 17671 ATHENS – GREECE
T. +30 210 95 70 222 | E. support@cosmoslac.com | W. www.cosmoslac.com
MADE IN GREECE

CERTIFIED QUALITY SYSTEM **ISO 9001**