TDS

CUT & DRILL OIL



DESCRIPTION

Lubricant for metal drills, cutting knifes and metal tapping Suitable for most metals, such as aluminum, brass and stainless-steel. Increases lifetime of metal drills and cutting knifes. Reduces wear and friction. Excellent Extreme Pressure and Anti Wear properties. Protects against oxidation and corrosion.

PROPERTIES

- Base: Mineral oils with extreme pressure (EP) and anti-wear (AW) additives
- Propellant: Propane - butane
- Appearance: Oily
- Pressure : 4 Bar (20°C)
- Spray pattern: Jet

INSTRUCTIONS FOR USE

APPLICATION
Use on room temperature Shake before use.
Before drilling, apply cutting oil to the drill bit and part being drilled.
Repeat if necessary.

SAFETY
See MSDS.
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Pressurized container: Do not pierce or burn, even after use.
Do not spray on an open flame or other ignition source.
Avoid breathing spray. Wear protective gloves / eye protection.
Use only outdoors or in a well-ventilated area.

WARRANTY
1 year after date of production.

APPLICATION TEMPERATURE
10°C - 25°C

AFTER USE
Spray holding the can inverted for 3''. Clean the caps with solvent.

STORAGE
Cool and dry (5°C - 35°C). Do not store in vehicles.

CAP SYSTEM



RED NEEDLE CAP
- Wide spray nozzle
- Penetrates in inaccessible narrow points
- No drips

SAFETY

Request SDS

ISSUED DATE: 2/7/25 **VERSION:** 01

This information was composed to the best of our current knowledge. It provides no guarantees.
The data in this sheet is a result of extensive testing either by Cosmos Lac or its suppliers.
However always thoroughly check whether the product is fit to serve the purpose you mean it to work for.

COSMOS LAC A.E.
PAINT INDUSTRY
©2025
PLITHONOS GEMISTOU 1, KALLITHEA 17671 ATHENS – GREECE
T. +30 210 95 70 222 | E. support@cosmoslac.com | W. www.cosmoslac.com
MADE IN GREECE

CERTIFIED QUALITY SYSTEM **ISO 9001**