



DESCRIPTION

Protective undercoat spray based on synthetic resins and rubber. Quick dry, anticorrosive, texture surface which protects the lower part of the car body from salt, bumps, and moisture. Soundproofing material lower car body. Can be overpainted.

PROPERTIES

- Viscosity: 25-35sec (Flow Cup DIN4, 20°C)
- Density: 1.0±0.03 g/L (Density Cup 100cm³/20°C, ASTM D – 1475)
- VOC content : 595 g/L
- Flash Point: -104°C
- Drying time
(1 Layer, Temperature 20°C, Humidity <65%):
 - Touch: 10-15min
 - Thorough dry: 1h
 - Maximum hardness: 24h
- Coverage: 2m²/L
- Gloss: 0-10 GLOSS UNIT/MATT
(GLOSS METER 60°ASTM D – 1471)
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 400ml

INSTRUCTIONS FOR USE

APPLICATION

Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on the testing surface. For better results apply 2-3 thin coats, 5-10 min apart.

Best application temperature: 10°C - 25°C.

AFTER USE

Spray holding the inverted for 3". Clean the caps with solvent.

STORAGE

5-35°C. Do not store inside vehicles.

CAP SYSTEM



WHITE FAT CAP

- High Coverage
- Even coating
- Fast drying
- Suitable for effects


SAFETY

Request SDS

*Cap indicates the color of the paint.

COLOR RANGE

250 WHITE



251 BLACK



252 GREY

