



DESCRIPTION

Transparent acrylic glossy varnish with glitter effect ideal for coated and uncoated surfaces such as wood, metal, and stone. This clear glitter lacquer has excellent adhesion, lasting gloss, and good weather resistance providing a sparkling finish for all decorative projects.

PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm³/20°C, ASTM D – 1475)
- VOC content : 600 g/L
- Flash Point: -104°C
- Drying time
(1 Layer, Temperature 20°C, Humidity <65%):
 - Touch: 5-10min
 - Through dry: 1h
 - Maximum hardness: 24h
- Coverage: 5m²/L
- GLOSS (GLOSS METER 60°ASTM D – 1471):
80-90 GLOSS UNITS
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 400ml

INSTRUCTIONS FOR USE

APPLICATION

Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart. **Best application temperature: 10°C - 25°C.**

AFTER USE

Spray holding the can inverted for 3'. Clean the caps with solvent.

STORAGE

5°C-35°C. Do not put in vehicles.

CAP SYSTEM



- WHITE FAT CAP (Female spray cap)
- High Coverage
 - Even coating
 - Fast drying
 - Suitable for effects

SAFETY

Request SDS

COLOR RANGE

EASY MAX | GLITTER SILVER
CL 900



EASY MAX | GLITTER GOLD
CL 901



EASY MAX | GLITTER MULTI
CL 902

