



## DESCRIPTION

Decorative quick drying paint giving the painted objects a fashionable sandstone effect. For the surface of metal, wood, plastic, polystyrene, stone, clay, ceramic, glass, paper and paperboard. To obtain a satisfactory effect, it is recommended to clean the surface you want to decorate, sand smoothly and apply a primer suitable for the surface.

## PROPERTIES

- VOC content : 620g/L
- Flash Point: -104°C (based on propellant)
- Drying time  
(1 Layer, Temperature 20°C, Humidity <65%):  
Touch: 1h  
Maximum hardness: 3 days
- Coverage: 2-3m<sup>2</sup>/L
- Contents: 400ml

## INSTRUCTIONS FOR USE

### APPLICATION

Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Before use, shake approx. 1min and perform the spray on a testing area. Apply thin layers from a distance of about 25-30cm from the surface. Keep a 10-15 min. interval between layers.

**Optimum application temperature: 16°C - 25°C.**

### AFTER USE

Spray holding the can inverted for 3''. Clean the caps with solvent.

### STORAGE

10-25°C. Do not put in vehicles.

## CAP SYSTEM



### WHITE FAT CAP (Female spray cap)

- High Coverage
- Even coating
- Fast drying
- Suitably for effects

## SAFETY

Request SDS

## COLOR RANGE

940 SAND EFFECT  
BEIGE



941 SAND EFFECT  
GREY



\*Cap indicates the color & texture of the paint.