

**DESCRIPTION**

High gloss white paint specially formulated for painting or renovating white aluminium surfaces. Based on acrylic resin performs high gloss and durability. The shade of white matches that used in electrostatic paint for aluminium items.

**PROPERTIES**

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm<sup>3</sup>/20°C, ASTM D – 1475)
- VOC content: 650 g/L
- Flash Point: -104°C (based on propellant)
- Drying time
  - Touch (20°C, Humidity<65%): 5-10min
  - Through dry (20°C, Humidity <65%): 1h
  - Maximum hardness: 24h
- Coverage: 5m<sup>2</sup>/L
- Gloss: 70-90 GLOSS UNIT  
(GLOSS METER 60°ASTM D – 1471)
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 400ml

**INSTRUCTIONS FOR USE****APPLICATION**

Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart.

**Best application temperature: 10-25°C.**

**AFTER USE**

Spray holding the can inverted for 3". Clean the caps with solvent.

**STORAGE**

Store between 5-35°C. Do not store in vehicles.

**CAP SYSTEM****SMART CAP**

- Less overspray
- Extreme Coverage
- Fast drying
- Hard chisel lines
- Even coating
- Suitably for effects
- Dual way spraying

**SAFETY**

Request SDS

**COLOR RANGE**

380 WHITE

