

**DESCRIPTION**

Special transparent primer for pre-treatment of plastic surfaces, difficult for painting. It is applied quickly. It offers high coverage and adhesion to all plastic surfaces. Ideal for all plastic parts of the car as well as for garden items such as plastic chairs, pots, etc.

**PROPERTIES**

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm<sup>3</sup>/20°C, ASTM D – 1475)
- VOC content: 688 g/L
- Flash Point: -104°C (based on propellant)
- Drying time
  - Touch (20°C, Humidity<65%): 10-15min
  - Through dry (20°C, Humidity <65%): 1h
  - Maximum hardness: 24h
- Coverage: 2m<sup>2</sup>/400ml
- Contents: 400ml

**INSTRUCTIONS FOR USE****APPLICATION**

Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. Apply the primer in several thin layers. For better results apply 2-3 thin coats, 3-5 min apart. **Best application temperature: 10-25°C.**

**AFTER USE**

Spray holding the can inverted for 3''. Clean the caps with solvent.

**STORAGE**

Store between 5-35°C. Do not store in vehicles.

**CAP SYSTEM****SMART CAP**

- Less overspray
- Extreme Coverage
- Fast drying
- Hard chisel lines
- Even coating
- Suitably for effects
- Dual way spraying

**SAFETY**

Request SDS