



DESCRIPTION

Rubberized coating that insulates and seals leaks. It creates a thick elastic layer that has high resistance to weather conditions and UV radiation. Ideal for roofs, balconies, drainage pipes, gutters, mezzanines. Applies to metal, vinyl, plastic, PVC, cement. It can be over painted with any paint after it has dried.

PROPERTIES

- Viscosity: 25-35sec (Flow Cup DIN4, 20°C)
- Density: 1.0±0.03 g/L (Density Cup 100cm³/20°C, ASTM D – 1475)
- VOC content : 595 g/L
- Flash Point: -104°C
- Drying time
(1 Layer, Temperature 20°C, Humidity <65%):
 - Touch: 10-15min
 - Thorough dry: 1h
 - Maximum hardness: 24h
- Coverage: 3m²/L
- GLOSS (GLOSS METER 60°ASTM D – 1471):
10 GLOSS UNITS/MATT
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 500ml

INSTRUCTIONS FOR USE

APPLICATION

Surfaces must be clean, dry, and free from grease. Cover the areas that need to be protected with tape. Shake the container for two minutes. Spray on a test area to check the distance (20-30cm) and technique of spraying. Apply at least one second layer after 15 minutes.

Best application temperature: 10°C - 25°C.

AFTER USE

Spray holding the inverted for 3". Clean the caps with solvent.

STORAGE

5-35°C. Do not store inside vehicles.

CAP SYSTEM



WHITE FAT CAP

- High Coverage
- Even coating
- Fast drying
- Suitable for effects

SAFETY

Request SDS

COLOR RANGE

SEALER 260

BLACK




SEALER 261

GREY



SEALER 262

WHITE



SEALER 263

BRICK RED



*Cap indicates the color of the paint.